



The RESU 6.4.EX allows for expansion with two 3.2Wh modules so you can have a 6.4 Wh or 9,6 or even 12.8Wh system. With such flexibility it is a great solution for households of many sizes.

The RESU 6.4 EX can be installed indoors and the unit can be mounted on sturdy walls easily





## Technical Specification

ltem	Description	
	Main Pack	Expansion Pack
Nominal Energy	6.4 kWh	3.2 kWh
Nominal Capacity (CC/CV Mode, Cut-off : 0.05C)	126 Ah	63 Ah
Dimension (Width x Height x Depth)	406 x 664 x165 mm	230 x 664 x165 mm
Weight	60 kg	30 kg
Max Discharge Current	110 A	
Nominal Voltage (DC)	51.8 V	
Voltage Range (DC)	45.2 V ~ 58.1 V	
Nominal Discharge Current	0.3C	
Nominal Charge Current	0.3C	
Peak Power (25 $^{\circ}$ C/77 $^{\circ}$ F)	5 kW	
Faradic Charge Efficiency (25 $^{\circ}$ C/77 $^{\circ}$ F)	99 %	
Battery Roundtrip Efficiency (C/3, 25 $^{\circ}$ C/77 $^{\circ}$ F)	95 %	
Expected Lifetime (25 $^{\circ}$ C/+77 $^{\circ}$ F)	> 10 years	
Cycle life (90% DOD, 25 $^{\circ}$ C/+77 $^{\circ}$ F)	> 6,000 cycle	
Available Operating Temperature	0 ~ 40 ℃	
Optimal Operating Temperature	15∼30℃	
Storage Temperature	-30 ~ 50 ℃	
Cooling	Natural Convection	
Interface	CAN, CANopen Communication	
Cell Safety	IEC 62133	
Pack Safety	UN 3480 Class 9 UN 38.3	
United Nation Class		
Hazard Classification		
Transportation Regulation Compliance		
Protection Class	IP 21	



## **Energy Solution Company ESS Business Division**

LG Twin Towers, 128, Yeouidaero, Yeongdeungpo-gu, Seoul 150-721, Korea

Changhwan Choi, Manager Tel.: 82-2-3773-3258 e-mail: cchoi@lgchem.com



Dealer Information